



Anglomoil Super Outboard Motor Oil is a current state of the art two stroke motor oil, suitable for high performance water cooled engines and for air cooled engines.

It is formulated from highly refined base oils blended with a synthetic component and ashless performance additives to meet the exacting requirements of the National Marine Manufacturers Association TC-W3 specification.

The oil has a viscosity of about SAE40 but it is diluted with a solvent to facilitate mixing and dispersion in the fuel.

Anglomoil Super Outboard Motor Oil is particularly suitable for large water cooled two stroke engines operating under severe conditions, eg high speed boats, water skiing. It can be pre-mixed with the fuel, or used in direct oil injection systems at the ratio recommended by the engine manufacturer.

Smaller, high performance air cooled motors can also benefit from the properties of Super Outboard Motor Oil, and it is recommended for chain saw motors and even racing go-cart motors!



- TC-W3 certified
- Maintains combustion chamber & exhaust system cleanliness
- Reduces smoke
- Protects against spark plug fouling
- Controls deposits and minimises wear
- Good solubility in fuel at all temperatures
- Protects against rusting
- Suitable for water cooled and air cooled engines
- Suitable for pre-mix in fuel or direct oil injection

Density at 15°C, kg/L	.8617
Viscosity, Kiematic, cSt	
at 40°C	40.9
at 100°C	7.09
Viscosity index	135.2
Sulphated Ash, mass%	Nil
Base number	5.2
Flash Point, at °C	98
Colour	Purple

Anglomoil Superior Lubricants

Lubricants for Automotive - Industry -Food - Farm Machinery - Marine - Earthmovers - Road Transport

2 Beaumont Rd,Mt Kuringai, NSW, Australia Phone: +61 2 9457 8566, Fax: +61 2 9457 8057 Email: info@anglomoil.com Web: www.anglomoil.com